



Lift Safety & Procedures

Only trained and authorized staff are permitted to position vehicles on lift arms and perform the initial raise of the vehicle.

Customers are free to raise and lower the vehicle to their desired working height once a staff member has placed the vehicle on the lift arms and completed initial raise. Under no circumstances is a customer to move or reposition the lift arms under the vehicle.

LOOK BEFORE LOWERING! Before releasing the load-holding device to lower the lift, remove toolboxes, jacks, oil drain catch can, service carts, creepers, and anything else from under the vehicle.

IF AT ANY TIME DURING YOUR VISIT YOU ARE UNSURE ABOUT LIFT FUNCTION OR SAFETY PROTOCOLS ASK A LUGNUTZ TEAM MEMBER FOR ASSISTANCE.

After the vehicle is raised to the desired working height, always lower the lift onto its load-holding devices, and visually check all vehicle contact points to make sure each adapter or support is securely in position before going under the vehicle.

Never raise or lower with a person inside the vehicle. Ensure other people are clear of the vehicle when raising or lowering.

The removal or installation of heavy components (e.g. a differential) may cause the raised vehicle to become unstable. Use vehicle support stands (tripods) for stabilizing the load.

Never operate the lift if it makes unusual noises. Ask a staff member to assist you if this occurs.

Do not tamper with, bypass, or otherwise attempt to override the operating controls. Operating controls are designed to return to the neutral, or off, position when released.

Lift the vehicle by 1-2 inches prior to starting the lowering procedure. This will bring the vehicle off its load-holding devices and is required to initiate the lowering procedure.

Release the locking latch by holding down the yellow locking latch lever. Hold the yellow lever down and press the lowering lever (located near the hydraulic fluid reservoir) simultaneously to begin lowering the vehicle.

Once vehicle is on the ground, ask a staff member to assist you with removing the lift arms and completing the check-out process.